

# Polyester



This series is made up of a series of cabinets manufactured in hot pressed polyester reinforced with fibre glass, halogen free, which gives the series a really high performance level.

There are IP66 cabinets, and are available in 7 different sizes, in RAL9002 grey colour. They are symmetric and reversible in many cases, thus obtaining a high degree of versatility for carrying all types of electric, pneumatic, hydraulic and communications installations, etc. The base is manufactured in just one piece thus guaranteeing optimum inner space and increasing its resistance to impact.

There are also cabinets which have an IP55 degree of protection (1000 (H) x 750 (W)), made in RAL7035 grey colour.

Its double insulation characteristics guarantee maximum safety both for the installations and for persons.

## ■ POLYESTER ENCLOSURES IP66-IP55



### TECHNICAL DATA IP66

■ degree of protection	IP66
■ resistance to impact	IK10
■ test of resistance to glow wire	960°C
■ thermic class	150°C
■ materials	Hot moulded fibreglass reinforced polyester (GRP)
■ colour	RAL 9002

*According to 2006/95/EC directive and UNE-EN 62208 and UNE-EN 60439-1-3 norms, on affected parts.*

### TECHNICAL DATA IP55

■ degree of protection	IP55
■ resistance to impact	IK10
■ test of resistance to glow wire	960°C
■ thermic class	150°C
■ materials	Hot moulded fibreglass reinforced polyester (GRP)
■ colour	RAL 7035

*According to 2006/95/EC directive and UNE-EN 62208 and UNE-EN 60439-1-3 norms, on affected parts.*

# features POLYESTER

## POLYESTER 66



### BUILT-IN / SURROUNDING PROTECTION EDGE

- Guarantee the possibility to open the door 180° in built-in installations.
- Avoid entrance of water while opening the door.
- Guarantee that the cabinet is straight in comparison with the surface.




### INTERNAL ZAMAK HINGE

- 180° door opening warranted. Corrosion free.

### EASY FITTING

- Quick fixture guides in the back.
- Permits fitting without drilling.



### VARIOUS CLOSING SYSTEMS

- Double bit (Standard), triangular screw and manual with key lock.

## POLYESTER 55

### TWO DEPTHS

- Available in two depths 300 and 420 mm.



### INTERNAL HINGES

- The internal hinges allow the door to be opened 105°.

### FASTENING SYSTEMS

- Several basic fastening methods can be used: wall, surface and with pedestal.



### VARIOUS LOCKING SYSTEMS

- Swing handle, double bit key lock, with key or triangular.

# POLYESTER IP66


## ■ IP66 CABINETS



### STANDARD LOCK

2x double bit DIN 3,0 mm

Supplied without the necessary accessories for direct wall mounting



### Commercial Ref.

	A	B	C	D	E
POL302514	300	250	140	276	212
POL403020	400	300	200	370	262
POL404020	400	400	200	370	362
POL504020	500	400	200	470	362
POL604023	600	400	230	570	362
POL605023	600	500	230	570	462
POL806030	800	600	300	770	562

**IP66**

## ■ MODULAR CHASSIS




Comprises a chassis, blind lids and DIN profiles


Commercial Ref.	Modules	Rows	Cabinet Ref.
PCH4030	24	2x12	POL403020
PCH4040	36	2x18	POL404020
PCH5040	54	3x18	POL504020
PCH6040	54	3x18	POL604023
PCH6050	69	3x23	POL605023
PCH8060	116	4x29	POL806030

# accessories POLYESTER IP66


## POLYESTER BASE PLATE ■

	Commercial Ref.		Cabinet Ref.
	PPL3025	4 mm thickness	300x250x140
	PPL4030	4 mm thickness	400x300x200
	PPL4040	4 mm thickness	400x400x200
	PPL5040	4 mm thickness	500x400x200
	PPL6040	4 mm thickness	600x400x230
	PPL6050	4 mm thickness	600x500x230
	PPL8060	4 mm thickness	800x600x300


## METAL BASE PLATE ■

	Commercial Ref.		Cabinet Ref.
	PML3025	2 mm thickness	300x250x140
	PML4030	2 mm thickness	400x300x200
	PML4040	2 mm thickness	400x400x200
	PML5040	2 mm thickness	500x400x200
	PML6040	2 mm thickness	600x400x230
	PML6050	2 mm thickness	600x500x230
	PML8060	2 mm thickness	800x600x300

## PLATES DIMENSIONS ■

Commercial Ref.	Commercial Ref.	A	B	C	D	
PPL3025	PML3025	268	213	248	175	
PPL4030	PML4030	358	260	338	222	
PPL4040	PML4040	358	360	338	322	
PPL5040	PML5040	458	360	438	322	
PPL6040	PML6040	558	360	538	322	
PPL6050	PML6050	558	460	538	422	
PPL8060	PML8060	754	556	734	518	

## INNER DOOR ■

	Commercial Ref.		Cabinet Ref.
	PPIN4030		400x300x200
	PPIN4040		400x400x200
	PPIN5040		500x400x200
	PPIN6040		600x400x230
	PPIN6050		600x500x230
	PPIN8060		800x600x300

# POLYESTER IP66 accessories

## ■ SURFACE MOUNTING



### Commercial Ref.

29221	4 wall fixing set with head-insulated screws
29222	4 set of adjustable brackets

## ■ ADJUSTABLE BASE PLATE



Set of four profiles for the adjustment of the base plate, to different depths

### Commercial Ref.

29223	For 200 mm depth cabinets
29224	For 230 mm depth cabinets
29225	For 300 mm depth cabinets

## ■ CLOSING PLATE



Are used for the entrance of cables, cable glands, etc.

### Commercial Ref.

29226	For 250 width (10 pcs. bag)
29227	For 350 width (10 pcs. bag)
29228	For 400/500 width (10 pcs. bag)

## ■ LOCKS




### Commercial Ref.

29229	Standard double bit lock
29230	Triangular screw 11 mm
29231	Manual with key lock
29266	Zinc blockage lock
48449	Double bit key



# POLYESTER IP55


## IP55 CABINETS ■



Commercial Ref.	Dimensions
POL1007530	1.000x750x300
POL1007542	1.000x750x420


IP55

## BASE PLATE ■



Commercial Ref.		Cabinet Ref.
PPL10075	Polyester base plate (fixed) (depth 300-420)	1.000x750
PML10075	Zinc metallic base plate (depth 300-420)	1.000x750
PPG1007530	Polyester base plate adjustable in depth and hinged (depth 300)	1.000x750
PPG1007542	Polyester base plate adjustable in depth and hinged (depth 420)	1.000x750


## STEEL PEDESTAL ■



Painted in black


Commercial Ref.		Cabinet Ref.
ZOC1007530	50 mm pedestal for 300 mm depth	1.000x750x300
ZOC1007542	50 mm pedestal for 420 mm depth	1.000x750x420

## SURFACE BRACKETS ■



Commercial Ref.	
29240	Group of 4 brackets made of Zinc Steel

## LOCKS WITH SWING HANDLE ■



Commercial Ref.	
29241	Standard double-bit lock
29242	Triangular screw 11 mm
29243	Manual with key look
48460	Double-bit zamak-key